OMFZ2 Component - Plastics	Monday, July 18, 2005	E19450

## LG MMA CORP

YUHWA SECURITIES BLDG, 12TH FL 23-7 YOIDO-DONG YOUNGDUNGPO-GU SEOUL 150-738 KR

Material Designation: HP-202

Product Description: Polymethyl Methacrylate (PMMA), furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
NC	1.5	НВ	-	-	50	50	50	-	-
NC	3.0	НВ	-	-	50	50	50	-	-
CTI: -	IEC CTI (V): -	HVTR: - D495: -				IEC Ball Pressure (°C): -			
Dielectric Strength (kV/mm): - ISO Tensile Strength (MPa): - ISO Tensile Impact (kJ/m²): -		<b>Volume Resistivity</b> (10*ohm-cm): - <b>ISO Flexural Strength</b> (MPa): - <b>ISO Izod Impact</b> (kJ/m²): -					Dimensional Stability(%): - ISO Heat Deflection (°C): - ISO Charpy Impact (kJ/m²): -		

Report Date: 7/12/2005 Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.