

LG MMA CORP

Tech-Team 759 Chungheg-Dong, Yeosu-Shi Chunnam-Do 555-805 KR

IH830L

Polymethyl Methacrylate (PMMA), furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC	1.5	HB	-	-	50	50	50
	3.0	HB	-	-	50	50	50
Comparative Tracking Index (CTI): -					Inclined Plane Tracking (IPT): -		
Dielectric Strength (kV/mm): -					Volume Resistivity (10 ⁹ ohm-cm): -		
High-Voltage Arc Tracking Rate (HVRT): -					High Volt, Low Current Arc Resis (D495): -		
Dimensional Stability (%): -							

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2016-09-21

Last Revised: 2016-09-21

© 2016 UL LLC



IEC and ISO Test Methods

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	1.5	HB75 (NC)
			3.0	HB40 (NC)
Glow-Wire Flammability (GWI)	IEC 60695-2-12	C	-	-
Glow-Wire Ignition (GWI/T)	IEC 60695-2-13	C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 6256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-